

MODEL : MGW SERIES

MOUNTAIN ROTAVATOR

MOUNTAIN
ROTAVATOR

- ✓ Designed for stable operation in mountainous and sloped terrain
- ✓ Provides consistent tillage performance even on uneven ground
- ✓ Equipped with high-strength side gears to reduce impact on the drivetrain
- ✓ Rear-following structure ensures uniform tillage across rough surfaces



Key Technology Highlights

- ✓ High-strength steel frame optimized for mountainous applications
- ✓ Rear frame with spring rod linkage absorbs shock and follows ground contours effectively
- ✓ Optimized blade arrangement reduces resistance and improves tillage efficiency
- ✓ Reinforced side gear system and durable blades enhance drivetrain protection and long-term reliability

MODEL			MACHINE SIZE (mm)			Weight	Flanges	Blades	Tilling Width	Tractor			
			Width	Length	Height	(Kg)	(Pcs)	(Pcs)	(mm)	(HP)			
											Change Gear	540RPM	1000RPM
WR	2050	MGW	2285	1030	1200	700	8	48	2050	70~90	24-16	103	191
	2150		2380			710			2150	75~100	21-19	140	259
	2250		2488			770			2250	80~100	*19-21*	171	316
	2350		2541			780	9	54	2350	85~110	16-24	232	429
	2500		2665			800			2500	90~120	*default settings		
	2600		2790			850			2600	95~120			
	2850		3030			900	11	66	2850	115~150			
	3050		3260			950	12	72	3050	120~175			

* Specifications are subject to change without prior notice.